

SULLAIR TSR-20 AIR COMPRESSOR

FOR THE RENTAL INDUSTRY

200 hp (160 kW) • 820–1051 cfm (23.2–29.8 m³/min) • 100–175 psi (7–12.1 bar)



Ideal For:

Emergency air

Standby air

Supplemental air

Peak load sharing

Rugged Package Design

- Suitable for outdoor application
- Self-contained package
- Cold weather protection
- Oil field skid
- Fluid containment pan
- Bearing fluid reservoirs
- Herisite coated coolers
- Fork lift pockets

- Heavy-duty, sound-attenuated enclosure
- Easy-access doors
- Heavy-duty air inlet filter
- Air-cooled package
- Stainless steel tubing
- Nema 4 electrical enclosure
- Wye-Delta starter

- Built-in circuit breaker
- Fully automated controls
- SupervisorTM controller
- RS-232 and RS-485 ports for communications & remote monitoring
- Cam lock electrical connections
- Genuine Sullube[®] fluid

- Broad operating temperature range: 20–120°F (-6.7–48.9°C)
- Multi-stage air/fluid separation
- Low fluid carry-over—1 ppm maximum

User-Friendly & Rental-Ready

- Spin-on fiberglass fluid filter
- Helical design drive gears
- Ball valve on air discharge



@Hitachi Global Air Power

SULLAIR TSR-20 TECHNICAL SPECIFICATIONS

Energy Savings

- Flanged Mounted Premium Efficient **TEFC Motor**
- Sullair Spiral Valve Capacity Control to help produce only the air you need



Sullair 10-Year Diamond Warranty

Confirming the Sullair rugged design and commitment to customer satisfaction, all new lubricated stationary air compressors (with discharge pressures up to 150 psi) include comprehensive extended warranty coverage:

- 10-year air end protection
- 5-year coverage on:
 - Motor
 - Aftercooler
 - Air/fluid receiver
 - Oil cooler

Maintaining the Sullair 10-Year Diamond Warranty requires using Genuine Sullair parts, Sullube® and participation in the oil sampling program. Restrictions apply.

FREQUENCY: 60 Hz

TSR-20 Model	200L	200H	200HH	200XH
Motor hp (kW)	200 (160)	200 (160)	200 (160)	200 (160)
Capacity cfm (m³/min)	1051 (29.8)	960 (27.2)	868 (24.6)	820 (23.2)
Pressure psi (bar)	100 (7)	125 (8.6)	150 (10.3)	175 (12.1)

FOR MORE INFORMATION, CONTACT YOUR LOCAL AUTHORIZED SULLAIR DISTRIBUTOR.

